TONTARRA



PRECISE & CONSISTENT SURGERY PROCEDURES

Reduction of friction through wave-like form

Fatigue-free surgery – smooth sliding, light-weight, breathable design

BEFORE & AFTER SURGERY NEITHER ASSEMBLY NOR DISASSEMBLY

One-piece model avoids the loss or mix up of instrument pieces during cleaning and sterilization

CLEANING VALIDATION: CERTIFIED WITH "EXCELLENT"

Simple, safe & time saving procedure

Easier identification of impurities and stains

CleanWave Laminectomy Punches

The CLEANWAVE Laminectomy punches are made of German stainless steal. Ceramic Coating ("CC") is available.

Punches with 2-6 mm width of bite have a bone ejector incorporated, only the punches with 1 mm width of bite come without ejector.





KERRISON WITH STANDARD FOOTPLATE - 40° up cut; 10 mm open A bone ejector is always incorporated into instruments with width of bite 2-6 mm

40° up cut; 10 mm open	Length of shaft		
	18 cm (7.2")	20 cm (8.0")	23 cm (9.2")
1 mm*	240-071-01-CW	240-072-01-CW	240-073-01-CW
2 mm	240-071-02A-CW	240-072-02A-CW	240-073-02A-CW
3 mm	240-071-03A-CW	240-072-03A-CW	240-073-03A-CW
4 mm	240-071-04A-CW	240-072-04A-CW	240-073-04A-CW
5 mm	240-071-05A-CW	240-072-05A-CW	240-073-05A-CW

*only available without ejector

Optional: also available with Ceramic Coating (CC)



The wavelike shape is not only advantegous during the cleaning process; it also leads to a significant reduction of friction of the sliding parts.



KERRISON WITH THIN FOOTPLATE

A bone ejector is always incorporated into instruments with width of bite 2-6 mm

40° up cut;	Length of shaft		
10 mm open	18 cm (7.2")	20 cm (8.0")	23 cm (9.2")
1 mm*	240-071-01T-CW	240-072-01T-CW	240-073-01T-CW
2 mm	240-071-02AT-CW	240-072-02AT-CW	240-073-02AT-CW
3 mm	240-071-03AT-CW	240-072-03AT-CW	240-073-03AT-CW
4 mm	240-071-04AT-CW	240-072-04AT-CW	240-073-04AT-CW
5 mm	240-071-05AT-CW	240-072-05AT-CW	240-073-05AT-CW

*only available without ejector

Optional: also available with Ceramic Coating (CC)

distributor for

Punches with thin floot plate are for delicate use only (e.g. cutting and removal of small bones - also retropulsed fragments - and soft tissue, and for working in stenotic areas.

KERRISON WITH CERAMIC COATING CC (STANDARD and THIN FOOT PLATE)

Ceramic coating elevates the hardness of the edges and adds to the strength of the punch for an even smoother action. The matte black finish is anti-reflective (reduced glare).

If you want to order ceramic coated KERRISONS, please add "CC" to the article number as shown in the examples below:

- · KERRISON Standard Footplate, width of bite 1 mm, length 18 cm (7.2"):
 - 240-071-01CC-CW
- KERRISON with thin Footplate, 5 mm:
 240-071-05ATCC-CW

Distributed in the UK by



7-9 Parkside Centre, Potters Way, Southend-on-Sea Essex SS2 5SJ T 01702 602050 E info@surgicalholdings.co.uk

